



INDUSTRIAL NOZZLES & SYSTEMS

Specialist Suppliers of Precision Spray Nozzles and Spraying Systems

ENGINEERING
YOUR SPRAY SOLUTION



Series	Description	Spray Angle	Max. Tank Diameter	Recommended Op. Pressure	Flowrate L/min	Max Temp.	Connection
566	MicroWhirly	180° & 360°	1.7m	2 bar	15-21	130°	3/8" BSPP M or F, 3/4" Slip-on
500.186	MiniWhirly – POM	300°	1.3m	2 bar	18	50°	1/2" BSPP F
500.191	MicroWhirly - PVDF	180°, 270°, 360°	1.1m	2 bar	13-20	90°	1/2" BSPP F
5NA	NanoSpinner	360°	1.6m	2 bar	15-20	140°	1/8" BSPP F
5MC	MicroSpinner	60°, 180°, 360°	1.8m	2 bar	23-39	140°	3/8" BSPP F, 1/2" Slip-on
5MI	MiniSpinner	60°, 180°, 360°	2.6m	2 bar	30-100	140°	3/4" BSPP F, 1/2" BSPP F, 3/4" Slip-on
594/ 595	Hygienic Whirly	360°	2.7m	3 bar	14-82	100°	3/8" BSPP F, 3/4" BSPP F, 3/4" Slip-on
569	Whirly	270°, 360°	3m	2 bar	48-145	140°	3/4" BSPP F, 3/4" Slip-on, 1" Slip-on, 1" Tri-clamp
573/ 583	Whirly - Teflon	180°, 270°, 360°	3.2m	2 bar	58-225	95°	3/4" BSPP F, 1" BSPP F, 3/4" Slip-on, 1" Slip-on
5S2/ 5S3	XactClean® HP	180°, 270°, 360°	8m	5 bar	40-213	95°	3/8", 1/2", 3/4" & 1" BSPP F, 1/2" & 3/4" Slip
515	ACCUClean	180°, 270°, 360°	8m	3 bar	118-237	140°	3/4" BSPP F, 1" BSPP F
5TA	IntenseClean Hygienic	360°	13m	5 bar	40-79	95°	3/4" BSPP F
5TB	IntenseClean Hygienic	360°	15m	5 bar	169-261	95°	1 1/2" BSPP F
5TM	IntenseClean	360°	23m	5 bar	198-411	60°	1 1/2" BSPP F
540/ 541	Static Spray Ball	240°	9.5m	3 bar	22-145	200°	1/2" BSPP F
591	Static Spray Ball Slip-on	180°, 360°	5.5m	3 bar	17-563	200°	DN8, 10, 15, 20, 25, 50